

Alumax

791C

Continuous Hinge Door and Panel



The Alumax 791C Stikstall Door and Panel adapts quickly and economically to virtually any shower opening from 36" to 60" wide.

Features include full length magnetic closure, continuous extruded ball and socket hinge that is integral to the hinge rail and jamb, and a horizontal drip trough that collects and drains remaining water back into the shower when the door is opened.

The 791C Door and Panel Stikstall enclosure is available in satin, silver, gold and brushed nickle anodized finishes, as well as, an array of powder paint colors including oil rubbed bronze.

791C Stikstall Shower Door - Framed



Distributor of
ALUMAX
BATH ENCLOSURES
by Sapa

PRODUCT FEATURES

Available in standard and custom configuration.
Tempered safety glass.
Door has a continuous extruded ball and socket hinge that is integral to the hinge rail and jamb.
Hinge assembly has a molded bushing attached at the top and bottom of door panel.

SIZE LIMITATIONS

Maximum allowable width of unit = 72
Maximum allowable height of unit = 84



PARTS LIST

- A. 1 Curb (with weep slots)
- B. 2 Wall Jamb
- C. 6 Plastic Wall Anchors
- D. 6 #8 x 1-1/2 Truss Head Screws
- E. 2 Plastic Setting Blocks
- F. 1 Fixed Glass Panel
- G. 1 180° Panel
- H. 1 Header
- J. 15 #6 x 3/8 Truss Head Screws
- K. 1 Glazed Door Panel
- L. 1 Strike Jamb (Magnetic)
- M. 2 Snap-in Fillers
- N. 1 Drip Rail
- P. 1 #6 x 3/8 Truss Head Screw
- Q. 2 Drip Plugs
- R. 1 Tapered Drip Vinyl
- S. 1 Roll of Double Stick Tape
- T. 1 Interior Door Handle
- U. 1 Exterior Door Handle
- V. 2 #6 x 1-1/8 Round Head Screw
- W. Vertical Glazing Vinyl
- X. Horizontal Glazing Vinyl

