

Alumax

794C Shower Door



The Alumax 794C Custom Stikstall Shower Door with a framed continuous hinge door is custom fabricated to exact opening dimensions. It easily adapts to buttress or odd angle conditions.

Features include full length magnetic closure, continuous extruded ball and socket hinge that is integral to the hinge rail and jamb, and a horizontal drip trough that collects and drains remaining water back into the shower when the door is opened.

The 794C Continuous Hinge Stikstall Shower Door is available in satin, silver, gold and brushed nickel anodized finishes, as well as, an array of powder paint colors including oil rubbed bronze.



Distributor of
ALUMAX
 BATH ENCLOSURES
 by Sapa

794C Stikstall Shower Door - Framed

PRODUCT FEATURES

Available in standard and custom configuration.
 Tempered safety glass.
 Pivot jambs to have a continuous vinyl seal.
 Top pivot pin to have safety washer to prevent accidental dislodging of the door.

SIZE LIMITATIONS

Maximum allowable width of unit = 72
 Maximum allowable height of unit = 84

PARTS LIST

- A. 3 Curb Sections (with weep slots)
- B. 4 135° Anchor Plates with Screws
- C. 17 #6 x 3/8 Truss Head Screws
- D. 3 Header Sections
- E. 2 Wall Jambs
- F. 6 Plastic Wall Anchors
- G. 6 #8 x 1-1/2 Truss Head Screws
- H. 4 Plastic Setting Blocks
- I. Continuous Hinge Jamb
- J. 2 Fixed Glass Panels
- K. 2 135° Post
- L. 1 Glazed Door Panel
- M. 1 Strike Jamb (Magnetic)
- N. 2 Snap-In Fillers
- O. Continuous Hinge Rail
- P. 1 Drip Rail
- Q. 2 Drip Plugs
- R. 1 Tapered Drip Vinyl
- S. 1 Roll Double Stick Tape
- T. 1 #6 x 3/8 Truss Head Screw
- U. 1 Interior Door Handle
- V. 1 Exterior Door Handle
- W. 2 #6 x 1-1/8 Round Head Screws
- X. Vertical Glazing Vinyl
- Y. Horizontal Glazing Vinyl

