

Alumax

795C Shower Door



The Alumax 795C Stikstall Panel, Door and Panel adapts quickly and economically to virtually any shower opening with a maximum of 60" width.

Features include full length magnetic closure, continuous extruded ball and socket hinge that is integral to the hinge rail and jamb, and a horizontal drip trough that collects and drains remaining water back into the shower when the door is opened.

The 795C Panel, Door and Panel Stikstall enclosure is available in satin, silver, gold and brushed nickel anodized finishes, as well as, an array of powder paint colors including oil rubbed bronze.



Distributor of
ALUMAX
 BATH ENCLOSURES
 by Sapa

795C Stikstall Shower Door - Framed

PRODUCT FEATURES

Available in standard and custom configuration.
 Tempered safety glass.
 Door has a continuous extruded ball and socket hinge that is integral to the hinge rail and jamb.
 Hinge assembly has a molded bushing attached at the top and bottom of door panel.

SIZE LIMITATIONS

Maximum allowable width of unit = 72
 Maximum allowable height of unit = 84



PARTS LIST

- A. 1 Curb Section
- B. 2 Wall Jamb
- C. 6 Plastic Wall Anchors
- D. 6 #8 x 1-1/2" Truss Head Screws
- E. 4 Plastic Setting Blocks
- F. 2 Fixed Glass Panels
- G. 2 180° Posts
- H. 1 Header
- I. Continuous Hinge Jamb
- J. 17 #6 x 3/8" Truss Head Screws
- L. 1 Glazed Door Panel
- M. 2 Snap-in Fillers
- N. 1 Strike Jamb (Magnetic)
- O. Continuous Hinge Rail
- P. 1 Drip Rail
- Q. 2 Drip Plugs
- R. 1 Tapered Drip Vinyl
- S. 1 Roll Double Stick Tape
- T. 1 #6 x 3/8" Truss Head Screw
- U. 1 Interior Door Handle
- V. 1 Exterior Door Handle
- W. 2 #6 x 1-1/8" Round Head Screws
- EE. Vertical Glazing Vinyl
- FF. Horizontal Glazing Vinyl

