

Alumax

395CV Stikstall Shower Door



The Alumax 395CV Custom Stikstall Shower Door with a frameless door is custom fabricated to exact opening dimensions. It easily adapts to buttress conditions.

Features include 1/4" glass door, a 6" back-to-back formed metal handle, magnetic closure and a clear vinyl drip rail, all of which adds an up-scale look to the bath environment.

The 395CV Stikstall Shower Door is available in brite silver, satin silver, gold and brushed nickel anodized finishes, as well as an array of powder paint colors including oil rubbed bronze.

395CV Stikstall Shower Door - Frameless



Distributor of **ALUMAX**
BATH ENCLOSURES
by Sapa

PRODUCT FEATURES

Available in standard and custom configuration.

Tempered safety glass.

Door has a continuous extruded ball and socket hinge that is integral to the hinge rail and jamb.

Hinge assembly has a molded bushing attached at the top and bottom of the door panel.

SIZE LIMITATIONS

Maximum allowable width of unit = 72"

Maximum allowable height of unit = 84"



PARTS LIST

- A. 1 Curb Section
- B. 2 Wall Jamb
- C. 6 Plastic Wall Anchors
- D. 6 #8 x 1-1/2" Truss Head Screws
- E. 4 Plastic Setting Blocks
- F. 2 Fixed Glass Panels
- G. 2 180° Posts
- H. 1 Header
- I. Continuous Hinge Jamb
- J. 14 #6 x 3/8" Truss Head Screws
- L. 1 Glazed Door Panel
- M. 2 Snap-in Fillers
- N. 1 Strike Jamb (Magnetic)
- P. 1 Handle Vinyl
- Q. Continuous Hinge Rail
- R. 1 Latch
- S. 2 Tubular Handles
- T. 4 Plastic Washers
- U. 2 Plastic Bushings
- V. 2 Cone Head Bolts
- W. 2 Set Screws
- X. 1 Deflector
- EE. Vertical Glazing Vinyl
- FF. Horizontal Glazing Vinyl

