


Alumax

793C

Shower Door



The Alumax 793C Custom Stikstall Shower Door with a framed continuous hinge door is custom fabricated to exact opening dimensions. It easily adapts to buttress conditions.

Features include full length magnetic closure, a continuous extruded ball and socket hinge that is integral to the hinge rail and jamb, and a horizontal drip trough that collects and drains remaining water back into the shower when the door is opened.

The 793C Continuous Hinge Stikstall Door is available in brite silver, satin silver, gold and brushed nickel anodized finishes, as well as an array of powder paint colors including oil rubbed bronze.

793C Stikstall Shower Door - Framed



Distributor of **ALUMAX**
BATH ENCLOSURES
by Sapa

PRODUCT FEATURES

Available in standard and custom configuration.

Tempered safety glass.


Door has a continuous extruded ball and socket hinge that is integral to the hinge rail and jamb.

Hinge assembly has a molded bushing attached at the top and bottom of the door panel.

SIZE LIMITATIONS

Maximum allowable width of unit = 72" x 36" x 36"

Maximum allowable height of unit = 84"



PARTS LIST

- A. 2 Curb Sections (with weep slots)
- B. 2 90° Anchor Plates
- C. 17 #6 x 3/8" Truss Head Screws
- D. 2 Header Sections
- E. 2 Wall Jamb
- F. 6 Plastic Wall Anchors
- G. 6 #8 x 1-1/2" Truss Head Screws
- H. 4 Plastic Setting Blocks
- I. Continuous Hinge Jamb
- J. 2 Fixed Glass Panels
- K. 1 90° Post
- L. 1 180° Post
- M. 1 Glazed Door Panel
- N. 1 Strike Jamb (Magnetic)
- O. Continuous Hinge Rail
- P. 2 Snap-in Fillers
- Q. 1 Drip Rail
- R. 2 Drip Plugs
- S. 1 Tapered Drip Vinyl
- T. 1 Roll Double Stick Tape
- U. 1 #6 x 3/8" Truss Head Screw
- V. 1 Interior Door Handle
- W. 1 Exterior Door Handle
- X. 2 #6 x 1-1/8" Round Head Screws
- Y. Vertical Glazing Vinyl
- Z. Horizontal Glazing Vinyl

